


# Decoding Depth of Meditation: Neurophysiological Insights from Expert Vipassana Practitioners

Reggente, N.<sup>1</sup>, Kothe, C.<sup>2</sup>, Nath, M.<sup>1</sup>, Brandmeyer, T.<sup>1,3</sup>, Hanada, G.<sup>1,3</sup>, Simonian, N.<sup>1,3</sup>, Mullen, S.<sup>1,3</sup>, Mullen, T.<sup>1,3</sup>

<sup>1</sup>Institute For Advanced Consciousness Studies, Santa Monica, CA, USA | <sup>2</sup>Intheon, San Diego, CA, USA | <sup>3</sup>BrainMind, San Francisco, CA, USA

## SHORT ON TIME? HERE'S THE SUMMARY

We decoded self-reported meditative depth across two sessions ( $\geq 1$  week between) in expert Vipassana practitioners ( $n=34$ ) using source-localized EEG in theta, alpha, and gamma bands along with Heart Evoked Potential amplitudes. Conventional EEG channel-level methods and a priori chosen brain regions failed to capture the complex, non-linear neural dynamics associated with varying meditation depths. We also introduce "spontaneous emergence" as an ecologically valid phenomenological sampling method, creating potential for multivariate, personalized neurofeedback.



Scan the QR Code for a PDF

## MOTIVATION

- To enhance EEG specificity for meditation neurofeedback, this study explores nuances within the meditative experience, going beyond differentiating meditation from other states (e.g., mind-wandering).
- Focusing on moment-to-moment "meditative depth" reporting in expert Vipassana practitioners, a high-dimensional, multivariate decoding approach is used to identify neural correlates of meditative gradations.
- Given the relationship between meditation and interoceptive awareness [1], this study also examines Heart Evoked Potentials as a function of meditative depth to further elucidate psychophysiological correlates.

## METHODS

- **Expert Vipassana practitioners** ( $n=34$ ;  $\mu_{\text{experience}}=16.15$  years, practicing  $\mu=6.53$  days/week, with  $\mu=82.38$  cumulative retreat days)
- 160 total minutes of meditation **across 2 sessions** ( $\geq 1$  week apart) with 2 blocks per session with **64-Channel EEG** (BrainProducts) & **Bio Peripherals** (CGX)
- Participants rated their meditative depth (1-5 button presses; shallow to deep) since their last report and confidence (1-5; low to high) using a finger-mounted clicker in separate blocks: spontaneously upon noticing mind-wandering ("**spontaneous emergence**") or when prompted by audio cues at  $\sim 4$ -minute jittered intervals ("**probe**"). For depth classification analyses, ratings with confidence  $\geq 4$  were included and epochs were extracted:
- Multiple source estimation methods (channel-based, sLORETA, generalized eigendecomposition, and deep learning) were compared using either spectral power or connectivity features in theta, alpha, and gamma bands. Models were evaluated using leave-one-participant-out cross-validation, with mean absolute error (MAE) for the continuous 1-5 scale and area under the receiver operator curve (AUC) for the two-level scale (low: 0-2, high: 4-5) as accuracy measures.
- For **Heart Evoked Potential** Analyses, EEG data were segmented into epochs **time-locked to the R-peak of the ECG**. One-way ANOVAs compared HEP amplitude across continual depth (1-5) and t-tests compared grouped depths (low: 1-2, high: 4-5).



## EEG Based Classifiers Can Decode Meditative Depth

Source Estimation Method	Measure	Continuous Depth (MAE, lower is better)	Low/High Depth (AUC, higher is better)
Channel-based (subset)	Power	1.501 +/- 0.372	0.634 +/- 0.159
	Connectivity	1.522 +/- 0.359	0.610 +/- 0.135
Channel-based (all)	Power	1.391 +/- 0.302	0.724 +/- 0.101
	Power	1.397 +/- 0.350	0.714 +/- 0.180
sLORETA	Power	1.457 +/- 0.330	0.684 +/- 0.150
	Power	1.426 +/- 0.516	0.722 +/- 0.150
Gen. Eigval	Power	<b>1.262 +/- 0.300</b>	0.754 +/- 0.110
	Connectivity	1.289 +/- 0.292	<b>0.807 +/- 0.117</b>
Deep Learning	Power	1.289 +/- 0.292	<b>0.807 +/- 0.117</b>
	Connectivity	1.335 +/- 0.313	0.798 +/- 0.128
EEGNet	N/A	1.329 +/- 0.385	0.756 +/- 0.157

Deep learning-informed source-localized ROIs using theta, alpha, and gamma band power achieved **81% depth decoding accuracy** for high (4,5) vs. low (1,2)

Generalized Eigendecomposition-informed source-localized ROIs using theta, alpha, and gamma connectivity achieved **1.2 Mean Absolute Error** in predicting continuous depth (1-5)


Scalp forward projections of learned EEG sources corresponding to the node connectivity weights between six spatial components estimated using the Generalized Eigendecomposition.



Participants provided **45% more ratings (with more confidence)** in the "spontaneous emergence" blocks with equivalent accuracy values to "probe".

## Heart Evoked Potential Amplitude Increases With Meditative Depth

Is this increased sensitivity to endogenous signals a mechanism underlying the increased interoceptive awareness and well-being accompanying meditation practice?



When using HEP-amplitude data, a Random Forest classifier achieved .63 MAE (1-5) and 91% Accuracy (High vs. Low)

## CONCLUSIONS

- Source-localized EEG power, Heart Evoked Potential amplitudes, and connectivity measures outperformed conventional methods in decoding self-reported meditative depth, revealing complex neural dynamics and heart-brain interactions.
- "Spontaneous emergence" proved to be a more ecologically valid and effective method for capturing self-reported depth compared to probing that yielded more responses and equivalent decoding accuracies.
- Decoding meditative depth feasibility is a critical step towards developing sophisticated, **multivariate neurofeedback** for effective meditation practice

## ACKNOWLEDGEMENTS

This work was made possible by an award from the the Tiny Blue Dot Foundation to NR.

THE TINY BLUE DOT FOUNDATION